

QUALPOL

HDPE CONDUIT

Raw Material

Manufactured using only
virgin resin.



Made to
ASTM F-2160
Dimensional Specifications

SPECIFICATIONS

SDR		3/4"	1"	1 1/4"	1 1/2"	2"	3"	4"
SDR9	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.818	1.023	1.292	1.478	1.847	2.722	3.500
	WALL	0.117	0.146	0.184	0.211	0.264	0.389	0.500
	WT/FT	0.150	0.230	0.360	0.480	0.750	1.360	2.688
SDR11	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.860	1.075	1.358	1.554	1.943	2.864	3.682
	WALL	0.095	0.120	0.151	0.173	0.216	0.318	0.409
	WT/FT	0.120	0.190	0.300	0.400	0.640	1.400	2.250
SDR 13.5	OD	0.000	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.000	1.121	1.414	1.618	2.023	2.982	3.834
	WALL	0.000	0.097	0.123	0.141	0.176	0.259	0.330
	WT/FT	0.000	0.160	0.260	0.340	0.530	1.160	1.910
SCH 40	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.784	1.009	1.340	1.570	2.027	3.016	3.970
	WALL	0.113	0.133	0.140	0.145	0.154	0.213	0.237
	WT/FT	0.150	0.220	0.290	0.350	0.470	0.960	1.380
SCH 80	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.702	0.915	1.232	1.452	1.887	2.828	3.746
	WALL	0.154	0.179	0.191	0.200	0.218	0.300	0.337
	WT/FT	0.190	0.280	0.380	0.460	0.640	1.310	1.914

Supply Options

Available on reels in custom
lengths and colors. Optional
features include stripes and
pull tape.

