

# QUALPOL

## HDPE CONDUIT

### Raw Material

Manufactured using only  
virgin resin.



Made to  
**ASTM F-2160**  
Dimensional Specifications

## SPECIFICATIONS

SDR		3/4"	1"	1 1/4"	1 1/2"	2"	3"	4"
SDR9	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.818	1.023	1.292	1.478	1.847	2.722	3.500
	WALL	0.117	0.146	0.184	0.211	0.264	0.389	0.500
	WT/FT	0.150	0.230	0.360	0.480	0.750	1.360	2.688
SDR11	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.860	1.075	1.358	1.554	1.943	2.864	3.682
	WALL	0.095	0.120	0.151	0.173	0.216	0.318	0.409
	WT/FT	0.120	0.190	0.300	0.400	0.640	1.400	2.250
SDR 13.5	OD	0.000	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.000	1.121	1.414	1.618	2.023	2.982	3.834
	WALL	0.000	0.097	0.123	0.141	0.176	0.259	0.330
	WT/FT	0.000	0.160	0.260	0.340	0.530	1.160	1.910
SCH 40	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.784	1.009	1.340	1.570	2.027	3.016	3.970
	WALL	0.113	0.133	0.140	0.145	0.154	0.213	0.237
	WT/FT	0.150	0.220	0.290	0.350	0.470	0.960	1.380
SCH 80	OD	1.050	1.315	1.660	1.900	2.375	3.500	4.500
	ID	0.702	0.915	1.232	1.452	1.887	2.828	3.746
	WALL	0.154	0.179	0.191	0.200	0.218	0.300	0.337
	WT/FT	0.190	0.280	0.380	0.460	0.640	1.310	1.914

### Supply Options

Available on reels in custom  
lengths and colors. Optional  
features include stripes and  
pull tape.

